



IWEISS

815 FAIRVIEW AVE #10
FAIRVIEW, NJ 07022
201-402-6500

KM Fabrics

FABRIC SPECIFICATIONS

Pattern Name	<u>Plateau/Apollo</u>	Pattern Number	<u>626</u>
Weight/Linear Yard	<u>12.9 Oz.</u>	Ground Yarn & Count	<u>150/66/1FR Poly</u>
Pile Yarn & Count	<u>150/66/1FR Poly</u>	Ground Weight	<u>0.120</u>
Pile Weight	<u>0.4313</u>	Ground Weight/ % of Total	<u>46%</u>
Pile Weight/ % of Total	<u>54%</u>	Ground Ends/Inch.	<u>51</u>
Pile Ends/Inch.	<u>51</u>	Filling Yarn & Count	<u>150/66/1FR Poly</u>
Pile Tufts/Sq. Inch.	<u>1785</u>	Filling Weight	<u>0.255</u>
Pile Height/1000"	<u>110</u>	Filling Picks/Inch	<u>105</u>

PERFORMANCE

This Fabric Meets or Exceeds The Listed Standard Requirements

<u>Test</u>	<u>Standard Requirements</u>	<u>Test Method</u>
Abrasion (Heavy Duty)	50,000 double rubs ANSI/ASTM-D-3597-02	ASTM-D-4157-02 Wyzenbeek Test
Tensile Strength:		
Warp:	50 Lbs. Min.	ASTM-D-1682
Filling:	50 Lbs. Min. ANSI/ASTM-D-3597-02	
Tear Strength:	6 Lbs. Min. 6 Lbs. Min. ANSI/ASTM-D-3597-02	ASTM-D-2262
Crocking:	Class 4 Dry Min. Class 3 Med. Min. ANSI/ASTM-D-3597-02	AATCC-8--2001
Light Fastness:	Fading 60 Hours	AATCC-16-2003

FLAMMABILITY

Manufactured To Meet The Following Requirements

NFPA 701
MVS 302
BIFMA F-1-1978
SC-191-53 Class1 California
UFAC Class 1