



IWEISS

815 FAIRVIEW AVE #10
FAIRVIEW, NJ 07022
201-402-6500

KM Fabrics, Inc.

FABRIC SPECIFICATIONS

Pattern Name	Prestige	Pattern Number	620
Weight/Linear Yard	27 oz.	Ground Yarn & Count	29/2 100% Trevira CS
Pile Yarn & Count	29/2 100% Trevira CS	Ground Weight	6.9 oz./L Yd
Pile Weight	13.2 oz./L yd.	Ground Weight/ % of Total	51%
Pile Weight/ % of Total	49%	Ground Ends/Inch.	48
Pile Ends/Inch.	26/ 51	Filling Yarn & Count	29/2 100% Trevira CS
Pile Tufts/Sq. Inch.	1224	Filling Weight	6.9 oz./L Yd
Pile Height/1000"	120	Filling Picks/Inch	48

PERFORMANCE

This Fabric Meets or Exceeds The Listed Standard Requirements

<u>Test</u>	<u>Standard Requirements</u>	<u>Test Method</u>
Abrasion (Heavy Duty)	15,000 double rubs ANSI/ASTM-D-3597-77	ASTM-D-1175-71-24 Wyzenbeek Test
Tensil Strength: Warp: Filling:	50 Lbs. Min. 50 Lbs. Min. ANSI/ASTM-D-3597-77	ASTM-D-1682
Tear Strength:	6 Lbs. Min. 6 Lbs. Min. ANSI/ASTM-D-3597-77	ASTM-D-2262
Crocking:	Class 4 Dry Min. Class 3 Med. Min. ANSI/ASTM-D-3597-77	AATCC-8-1974
Light Fastness:	Fading 60 Hours	AATCC-16A-1974

FLAMMABILITY

Manufactured To Meet The Following Requirements
MVS 302
BIFMA F-1-1978
SC-191-53 Class1 California
UFAC Class 1